

rivet tapes

Adhesive Tapes with Aggressive Tack and Strong Hold



Appliance/
White Goods

Building &
Construction

Industrial &
Fabrication

Sign &
Display

Transportation &
Recreational
Vehicles



Rivet Tapes are engineered to grip fast and deliver lasting hold. With high-strength, rubber adhesive, Rivet Tapes can replace traditional metal fasteners in many industrial applications. A variety of adhesive coating weights and widths together with the perfect combination of peel, tack and shear, make Rivet Tapes the ideal bonding solution for nearly any surface.

macbond®

mactac®
ALINTEC COMPANY



rivet tapes

Adhesive Tapes with Aggressive Tack and Strong Hold

Features

- Solvent-free, high-strength, rubber, pressure sensitive adhesive
- Available in 5 mil to 50 mil adhesive thicknesses and .5" to 11.5" adhesive widths
- Rolls are manufactured with ungummed edges for ease of application
- MTO & custom sizes will ship in 10-15 working days

Benefits

- Immediate bond to most surfaces from smooth to textured
- Extremely durable and able to replace mechanical fasteners in many applications
- Thinner coatings are ideal for POP or craft assembly, thicker coatings are ideal for panel assembly, vibration dampening and moisture resistance
- Holds materials in place for support and alignment in assembly applications
- Ideal for use with metal, wood, polyethylene, polypropylene, glass and corrugated materials

Part Number	Adhesive	Caliper (Mils) Adhesive	Adhesive Width	Liner Width	Roll Length	MOQ Rolls	Rolls/ Carton	Stock/ MTO
GS1001	GS Ultra High Tack	20	1.00"	1.50"	200'	8	8	Stock
GS1003	GS Ultra High Tack	20	.50"	1.00"	200'	12	12	Stock
GS1004	GS Ultra High Tack	35	.50" (RR)	2.00"	200'	72	6	MTO
GS1007	GS Ultra High Tack	35	1.00"	1.50"	200'	8	8	Stock
GS1013	GS Ultra High Tack	20	2.00"	3.00"	200'	4	4	Stock
GS1019	GS Ultra High Tack	35	0.75"	1.50"	200'	96	8	MTO
GS1023	GS Ultra High Tack	15	1.00"	1.50"	200'	96	8	MTO
GS2123200	GS Ultra High Tack	10	2.00"	3.00"	200'	36	4	MTO
GS2145-SC	GS Ultra High Tack	10	4.00"	5.00"	1350'	16	16*	MTO
GS2003	GS Ultra High Tack	5	0.75"	1.20"	900'	30	10	MTO
GS2004	GS Ultra High Tack	5	1.00"	1.50"	900'	24	8	MTO
GS2208	GS Ultra High Tack	15	4.00"	6.00"	400'	36	2	MTO
GS2313	GS Ultra High Tack	20	1.00"	1.20"	200'	120	10*	MTO
GS2603RR	GS Ultra High Tack	35	(2) @ .75" (RR)	3.00"	200'	48	4	MTO
GS2906	GS Ultra High Tack	50	2.00"	2.40"	150'	160	5	MTO

(RR)= 2 lanes of adhesive * Packed on pallets

Performance Characteristics

Test	Units	Typical Values
Quick Tack	lbs/sq in	20+
Peel Adhesion	lbs/in	22+
Shear	hours to fail	300+
Application Temp	degrees F	+50
Service Temp	degrees F	0 to 180

For Regulatory Information, please visit www.mactac.com for all product regulatory compliance.

For Quality information, please visit www.mactac.com/quality for all manufacturing site ISO 9001 certificates.

For Technical Data Sheets please visit www.mactac.com/industrialtapes.

Mactac is a member of the following organizations:
Gasket Fabricators Association
Pressure Sensitive Tape Council



Customer Service 800-548-3456

Mactac North America | 4560 Darrow Road, Stow, OH 44224-1898

email mactac.americas@mactac.com • www.mactac.com/industrialtapes