

Macbond® Differential Tapes

Engineered Tapes & Laminates

Bag Closure Tape

Credit Card
Mailers

Shelf Marking

POP &
Promotional
Displays

Gaskets




Mactac® is a leading supplier of double sided tapes for industry. Our line of differential double sided tapes offers a range of performance options.



Macbond® Differential Tapes

Engineered Tapes & Laminates

Minimum App Temperature +50°
Service Range: -40°F to 180°F (-40°C to 82°C)



Double-Coated Tapes

Construction							Master Roll		Performance Characteristics		
Part Number	Carrier	Adhesive	Coat Weight Mils		Liner	End Use	Width	Length	Peel SS (U) lbs/in	Tack SS (L) lb/sq.in	Shear hours
			Liner	Unwind		Release					
IB5121-72	.5 mil PET	XT / Low Tack Acrylic	1.0	1.2	72# White PCK	Medium	60"	750'	9.0	0.5	500+
IB5131-72	.5 mil PET	XT /Agressive Removable	1.0	1.2		Medium	60"	750'	9.0	2.0	500+
IB5161-72	.5 mil PET	Permanent 899 / Low Tack Acrylic	1.0	2.0		Medium	60"	750'	8.5	0.5	500+

For Regulatory Information, please visit www.mactac.com for all product regulatory compliance.
For Quality information, please visit www.mactac.com/quality for all manufacturing site ISO 9001 certificates.

For Technical Data Sheets please visit www.mactac.com/industrialtapes.

Mactac is a member of the following organizations:
Gasket Fabricators Association
Pressure Sensitive Tape Council

© 2024 Morgan Adhesives Company, LLC
MAC4182 (01/24)
Mactac and Macbond are trademarks of Morgan Adhesives Company, LLC

mactac 
A LINTEC COMPANY

Customer Service 800-548-3456

Mactac North America | 4560 Darrow Road, Stow, OH 44224-1898
email mactac.americas@mactac.com | www.mactac.com/industrialtapes