

macbond®

HBA724 acrylic

Applications

Automotive Interior Bonding | Heavy Machinery | RV Interior

Insulation and Sound Damping | General Bonding

Gasket & Seals | Fabrication & Assembly



Automotive



Recreational Vehicles



Insulation



Acoustic Tiling



General Assembly



Gaskets



Fabrication



Features

- High Bond Acrylic Adhesive
- Conformable Tissue Carrier
- Moisture Stable PCK liner

Benefits

- High initial tack
- Excellent adhesion to a wide variety of substrates
- Good LSE performance
- Dimensionally stable liner is easy to handle and resists moisture
- **Low VOC:** Meets JIS A 1901 standards for critical substances
- **Low Fog/Low Odor:** Tested in accordance with SAE J1756 guidelines

We're Solid.
100% 

mactac®
Industrial Tapes and Adhesives

Mactac® is a pioneer in 100% solids adhesive technology bringing solutions that stick to the industrial tape and adhesive market since 1959.

macbond®

HBA724 acrylic

Products Featuring HBA724 Acrylic Adhesive

Application Temperature Above 50°F (10°C) for best performance
End Use Temperature -40°F to 225°F continuous exposure
-40°F to 350°F intermittent exposure

Tissue Supported Acrylic Adhesive								
		Thickness			Master Roll		Performance Characteristics	
Part Number	Carrier	Carrier + Liner	Liner	Width	Length	Peel SS lb/in	Tack SS lb/sq.in	Shear hours
IB7372-74	Tissue	5.0 mils	74# PCK	54"	750'	5.9	7	300+

HBA724 complies with all REACH and RoHS regulations

HBA724 Adhesive meets the following criteria:

- FDA 21 CFR 175.125 (a) and (b)
- REACH and RoHS regulations
- Prop 65 compliant
- Consumer Product Safety Improvement Act of 2008

For additional Performance Guides on HBA724 products, please visit www.mactac.com.

Mactac is ISO9000-2015 certified.

Mactac is a member of the following organizations:

Gasket Fabricators Association
National Association of Graphic and Product Identification Manufacturers, Inc. (GPI)
Pressure Sensitive Tape Council (PSTC)

