

Short/Medium-term Signage

Product Guide



Elevate your signage strategy with Gruv GV400 & GV500 series print media which offers high-quality solutions for many graphic applications.

















Short/Medium-term Signage

Product Guide

What are Gruv™ 4 & 5?

Elevate your signage strategy with the **Gruv GV400 & GV500 series**. Crafted with air-egress vinyl media, it guarantees easy installations for captivating wall and signage applications. This is the product you need for wall and signage decals that endure the test of time.

Long-lasting: With up to 4-5 years of durability, your graphics will maintain their appearance over an extended period. Create eye-catching point-of-purchase decals and wall graphics.

Product Code	Face	Adhesive	Liner	Width	Durability	Recommended Overlamines	
						Promogard® PG7000	Colorgard® LUV
GV428PW54L150	 Matte White Opaque	Permanent	90# Air-egress	54"		■	■
GV429PW54L150	 Gloss White Opaque	Permanent	90# Air-egress	54"		■	■
GV429RW54L150	 Gloss White Opaque	Removable	90# Air-egress	54"		■	■
GV528PW54L150	 Matte White Opaque	Permanent	90# Air-egress	54"			■
GV529PW54L150	 Gloss White Opaque	Permanent	90# Air-egress	54"			■
GV529RW54L150	 Gloss White Opaque	Removable	90# Air-egress	54"			■

The film is designed for solvent, latex, and UV wide-format printing. It is coated on one side with either a permanent or removable opaque, acrylic pressure sensitive adhesive and supplied with a 90# polycoated air-egress release liner.

Durability

- Use-life estimate based on accelerated age studies on vertical applications under "normal" environmental conditions.
- Severe environmental conditions will reduce life expectancy.
- Recommendations are believed to be accurate but do not constitute a warranty written or implied. Refer to Mactac® Product Performance Guides and Technical Assistance Bulletins prior to use. Visit mactac.com to download.

Temperature Ranges

- Minimum Application: +50°F (+10°C) - End Use: -40 to 180°F (-40 to 82°C), except GV429R: -40 to 158°F (-40 to 70°C)

Shelf Life

Two years when stored at 60/77°F (15/25°C) and 50% relative humidity in the original package.

ICC profiles can be downloaded at mactac.com For more information about Gruv or other Mactac products, partnerships or graphic solutions, e-mail Mactac.Americas@mactac.com or visit mactac.com/graphics.